

DESIGNED with perforations to the base, shelves and top, to allow heated air flow to rise through the unit.

MANUFACTURED with detached plinth for maintenance access.

Image shows, full length single door unit includes hanging rail, 2 coat hooks and shelf.



Tubular Heating Unit

HEATED STEEL LOCKERS

HEATED LOCKER OVERVIEW

Transform indoor spaces with heated lockers: engineered to dry damp clothing while providing unmatched storage and security.



Perfect for workplaces, gyms, and facilities needing efficient, secure storage solutions to keep gear ready and dry

The perforations allow the heat to rise through the locker unit, allowing moisture to evaporate, helping damp items to dry.

Products are made to order, so your order gets the attention to detail it deserves.

Please call **02920 859600** or email info@garran-workspaces.co.uk for your personalised quote, tailored to meet your specific requirement.

Our Standards and Awards. Inspiring Confidence.



HTT Range

Thermostatic Heat Tube



Technical Details

Construction	Powder coated steel tube construction. Plastic endcaps.
Controls	Built in adjustable thermostat.
Thermostat	5°C To 40°C.
Element	60W, 240V, 50Hz. 120W, 240V, 50Hz. 180W, 240V, 50Hz. 240W, 240V, 50Hz.
Installation	Supplied with wall brackets. Supplied with fixing clips.
Safety	Auto reset thermal overload and thermal fuse.
IP Rating	IP44
Class	1
Cable	Pre-wired with 0.9m cable.
Colour / Finish	White steel body with grey endcaps.

Approvals	CE
Warranty	2 year exchange

Product Description

The Eco Thermostatic Tubular Heaters incorporate a built-in adjustable thermostat for flexible operation and energy saving over traditional tubular heaters. This makes them ideal for use in Drying Lockers and Wardrobes. Robust steel construction with high-quality white powder coated finish, and available in four industry- standard outputs.

Note: If individually heated lockers are required, the minimum locker width is 500mm.

Key Features

- 4 loadings/outputs - 60-240W.
- Adjustable thermostat. Frost protection.
- Wall or floor mounting - brackets supplied.
- Guard available for each size tube.

Dimensions

Model	No.	Output W	Height mm	Width mm	Depth mm	Weight kg
HTT1		60	80*	325	80*	0.5
HTT2		120	80*	630	80*	0.5
HTT3		180	80*	930	80*	1.5
HTT4		240	80*	1230	80*	1.5

*Dimensions above including mounting brackets.
Diameter of tube - Ø55mm

STEEL PAINT

DOOR / CARCASE FINISHES

Paints unless detailed below are MATT finish - 30% Gloss.
 Feature BioCote antimicrobial technology which reduces the presence of microbes by up to 99.99%. BioCote is permanent and complements existing cleaning practices.



STANDARD COLOURS



BLACK
GAK-MN204E



IRIS
GAK-EJ201E



WHITE RAL 9003
GAK-MA585E



IRISH
GAK-EK280E



LIGHT GREY
GAK-EL206E



CORNFLOWER
GAK-EJ203E



POPPY
GAK-EG290E



FLINT
GAK-EL209E

PREMIUM COLOURS - OPTIONAL EXTRA - MOQ 10* Units



SILVER TEXTURE
GAK-MW333E



GLACIER
GAK-EK216E



HEATHER
GAK-EH227E




PEARL
GAK-ED204E



CHOCOLATE
GAK-EM210E



PINE GREEN
GAK-EF200E



CLEAR LACQUER
FINISH



REEF
GAK-EK221E



DAFFODIL
GAK-EE250E



SAND
GAK-EE220E



PASTEL ORANGE
RAL 2003
*MOQ 20



SILVER
RAL 9006

Clear lacquer, BioCote antimicrobial coating not included.